

Introducing Non-Clean Press Oil

Non-Cleaning Press oil

Non-Clean Press oil (0% non-volatile content)

This series uses completely dry press oil, and the oil content disappears after processing, so there is no need for a cleaning process. Has already been well received in many thin plate press processing situations, such as eliminating ODS solvent cleaning in environmentally conscious production processes and applying it to surfacetreated steel sheets that are widely used mainly in the home appliance industry.

- Cost reduction achieved by omitting the cleaning process.
- Painting, printing, plating, labeling, screw tightening, resin installation, etc. can be done without cleaning.
- Free the work site from oil stains.

For surface treatment steel plate/copper plate materials

Product name	Application
G-6215F	Suitable for thin plate processing such as contact and electronic component punching and bending.
G-6215FS	G-6215F's improved lubricity type allows tapping.
G-6215FA	Improved dry type of G-6215FS.
G-6221F	Has particularly excellent seizure resistance and can be used for punching and bending SUS.
G-6221FA	Quick-drying improved type of G-6221F.
G-6231F	Totally balanced high performance product with high lubricity, quick drying, and tap.

sales@lubetech.co.th



For Aluminum plate material

Product name	Application
G-6216F	This type focuses on aluminum machining and takes lubricity into consideration, and tap machining is also possible.
G-6216FA	Suitable for fin processing, punching, bending, and tapping.
G-6216FS	Suitable for processes with slow drying with many stages.

For sheet drawing of various materials

Product name	Application
G-6280	Suitable for punching, bending, and light drawing of galvanized steel sheets.
G-6281	Suitable for punching, bending, and light drawing of steel plates (including stainless steel).
G-6284	Effective for bending and drawing with emphasis on aluminum processing.
G-6286	Effective for punching, bending, and drawing thick plates. Forced drying required.

22nd FL., Paso Tower, 88 Silom Rd., Suriyawong, Bangrak, Bangkok 10500, Thailand TEL: 0-2634-3855 FAX: 0-2634-3856